



PRODUCT-DETAILS

XF16/30M

XTRA FLEX 16MM REELED



General Information

Extended Product Type	XF16/30M
Product ID	7TCA296060R0101
EAN	5020963001321
Catalog Description	XTRA FLEX 16MM REELED
Long Description	Standard Weight Conduit, Nominal Conduit Size 16mm, Outside Diameter 16.5mm, Inside Diameter 12.0mm, Static Bend Radius 30mm, Reel Length 30 Meters, PVCu Spiral with Plasticised PVC Covering, Black

Ordering

EAN	5020963001321
Customs Tariff Number	3926909990

Dimensions

Product Net Weight	5.62 lb 2.549 kg
--------------------	---------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	1 in 25 mm

Package Level 2 Height	1 in 25 mm
Package Level 2 Depth / Length	1 in 25 mm

Additional Information

Application	Indoors / Outdoors, Torsional Equipment
Brand / Label	Adaptaflex
Color	Black
Flexibility	Very High
Inside Diameter	12.0 mm
Material	PVCu Spiral with Plasticised Covering
Nominal Size	16 mm
Number of Batteries	0
Outside Diameter	16.5 mm
Product Name	ADAPTAFLEX
Product Type	Standard Weight Conduit
Radius	30 mm
Special Functions	High UV Protection
UPC	786210253312

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	XF16/30M
Declaration of Conformity - CE	9AKK107492A9618
Instructions and Manuals	XF16/30M

Classifications

ETIM 6	EC001175 - Corrugated plastic hose
ETIM 7	EC001175 - Corrugated plastic hose
UNSPSC	39131706
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5535 >> Electrical conduit

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

