



PRODUCT-DETAILS

TY25M-2

CABLE TIE 50LB 7IN RED NYLON



General Information	
Extended Product Type:	TY25M-2
Product ID:	7TAG009270R0011
EAN:	5414363062516
Catalog Description:	CABLE TIE 50LB 7IN RED NYLON
Long Description:	High Performance Cable Tie for Indoor applications, Red Color Nylon 6.6, Length of 186mm (7.3 Inches) for Bundle Diameter up to 48mm (1.89 Inches), Width of 4.9mm (0.19 Inches), Tensile Strength Rating of 222 Newtons (50 Pounds), Operating Temperature of -60 Degrees Celsius (-76 F) to 85 Degrees Celsius (185 F), UL/EN/CSA62275 Type 2/21S Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Military Specified (MIL-SPEC MS3367-1-2), Bulk Pack
Display Name:	TY25M-2

Eco Transparency	
Environmental Product Declaration - EPD: 9AKK108469A9844	

Ordering	
----------	--

E-Number (Finland):	1381483
EAN:	5414363062516
UPC:	786210844855
Country or Territory of Origin:	United States
Selling Unit of Measure:	each

Dimensions

Product Net Width:	0.19 in 4.9 mm
Product Net Depth / Length:	7.2 in 183 mm

Container Information

Package Level 1 Units:	1000 EA
Package Level 1 Width:	0 mm 0 in
Package Level 1 Height:	0 mm 0 in
Package Level 1 Depth / Length:	0 mm 0 in
Package Level 2 Units:	10000 EA
Package Level 2 Width:	340.36 mm 13.4 in
Package Level 2 Height:	256.54 mm 10.1 in
Package Level 2 Depth / Length:	535.94 mm 21.1 in
Package Level 3 Units:	350000 EA
Package Level 3 Width:	0.025 mm 0.001 in
Package Level 3 Height:	0.025 mm 0.001 in
Package Level 3 Depth / Length:	0.025 mm 0.001 in

Technical UL/CSA

Flammability According to UL94:	V-2
---------------------------------	-----

Additional Information

Brand / Label:	Ty-Rap
Bundle Diameter:	0.12 to 1.89 in 3 to 48 mm

Color:	Red
Effective Date:	19680313
Lock Type:	Stainless Steel Barb
Material:	Nylon/Polyamide 6.6
Product Name:	Other
Product Type:	High Performance
Special Functions:	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless steel locking device insures both maximum strength and the right tightness every time.
Standards:	UL E49405
Tensile Strength:	50 lb 222 N
Thickness:	0.05 in 1.3 mm

Certificates and Declarations

Data Sheet, Technical Information:	TDS000518
Declaration of Conformity - CE:	9AKK107492A9841

External Classifications and Standards

ETIM 7:	EC000046 - Cable tie
ETIM 8:	EC000046 - Cable tie
ETIM 9:	EC000046 - Cable tie
ETIM 10:	EC000046 - Cable tie
UNSPSC:	39121703
IDEA Granular Category Code (IGCC):	5034 >> Cable ties

Material Compliance

RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Information:	False - does not contain substances > 0.1 mass percentage
WEEE Category:	Product Not in WEEE Scope

Categories

Products > Low Voltage Products and Systems > Installation Products > Wire Management and Connectivity > Cable Ties

